



TIP TRAILER

12 TO 20 TONNES

Our trailers are engineered to perform on your farm. The single-acting ram design provides low stress, stable lifting without twisting, and all trailers have a rugged tandem axle design. These are solid and dependable 12 - 20 tonne trailers that will help you share the load.

Call 0800 804 458 to find your local dealer.

To view the full list of features and optional extras, visit
www.giltrapag.co.nz.

KEY FEATURES

- Tailgate with automatic tailgate release and spreading chains
- Steep tipping angle to 55°
- High ground clearance when tipped
- Low deck height
- Replaceable bushes on main axle pivot
- Rugged 2-piece (3mm) removable pressed sides
- Removable front board
- Built-in heavy duty tie rails
- Treated 35mm T & G pine deck for excellent durability
- Single telescopic ram (with hard chromed stages) to lift efficiently and prevent deck twisting (two rams on 20 tonne)
- 4-way pivot on the ram base mount to prevent side-loading damage

OPTIONAL EXTRAS

- Brakes
- Hydraulic tailgate release
- 5mm steel deck
- 2mm steel overlay floor
- 900mm hay extension
- Top loading silage cage with drop front
- LED tail lights
- Sprung drawbar (except 12 tonne model)
- Optional wheel assemblies



The steel taildoor features a high clearance pivot and adjustable check chains for accurate spreading.



3mm two piece drop-in sides, with solid reinforcing posts for extra strength.



Two way pivot on the multistage ram base eliminates side loads between the stages which can otherwise score the cylinders and damage oil seals.



OPTIONAL SILAGE CAGES
Light but strong construction with automatic power gate for maximum unloading clearance. These silage cages have many innovative features and can be dismantled easily for shed storage.



A clever rear pivot design gives high ground clearance and keeps the load centre well forward when the deck is raised, leaving weight on the drawbar. Tipping angles are up to 57° for a clean dump.



Greasable swivel hitches and provision for safety chains ensure safety in the field.

MODEL	T54-12	T64-15	T68-17	T10-20
Deck (L x W)	4.4m x 2.4m	4.7m x 2.4m	5.0m x 2.4m	5.0m x 2.7m
Capacity	5.4m ³	6.4m ³	6.8m ³	10.2m ³
Rated Lift	12 tonnes	15 tonnes	17 tonnes	20 tonnes
Overall Length	5.95m	6.35m	6.50m	6.50m
Wheels	15/70 x 18	405/70 x 20	405/70 x 20	550/60 x 22.5
Ram Diameter	127/107/91/76/61	127/107/91/76/61	127/107/91/76/61	127/107/91/76/61
No. Ram Stages	5 Stage Tele	5 Stage Tele	5 Stage Tele	5 Stage Tele x 2
Side Board Height	600mm	600mm	600mm	800mm
Tare Weight	2700kg	3430kg	3750kg	4500kg
Deck Height	1200mm	1200mm	1200mm	1200mm
Axle Size	80mm (8 stud)	90mm (8 stud)	90mm (8 stud)	100mm (10 stud)
Jack Size	80	80	80	80
Silage Cage Capacity	22.7m ³	24.3m ³	25.9m ³	29.3m ³