



TIP TRAILER

HEAVY DUTY SERIES

The Heavy Duty series is designed for construction & earthworks where dump truck access may be limited. It makes it a cost-effective solution for difficult jobs.

Call 0800 804 458 to find your local dealer.

To view the full list of features and optional extras, visit www.giltrapag.co.nz.

KEY FEATURES

- Heavy duty construction
- Large cubic capacity
- 6mm folded steel floor and sides
- Sprung drawbar
- 25 tonne rated swivel towing eye
- 4-way pivot on the ram base mount to prevent side-loading damage
- Hydraulic brakes (front axles)
- Dual cross-over safety chains
- Lights
- Bushed tandem axles
- 15° angled floor to contain the load
- 1200mm rear tipping clearance

OPTIONAL EXTRAS

- Optional rear tail door with double acting hydraulic rams



Optional hydraulic rear tailgate with twin double acting rams and an enormous opening clearance of 1.2 metres.



15° rear deck angle keeps material firmly in the trailer, even without a tailgate and gives a high tipping clearance for building stockpiles.



The heavy duty tandem axle is standard with front drum brakes and oscillating beams with replaceable oil impregnated nylon bushes. Large flotation wheels stay on top of the ground, offering traction even on difficult sites.



Packed with safety features, HD trailers are standard with braking systems, tail lights, crossover safety chains and swivel hitches for ultimate operator safety and comfort.



The sprung drawbar reduces shock loading to the tractor towbar, ensuring a smooth power transfer from tractor to trailer and greater operator comfort.



A massive 70° tipping angle with long multi-stage rams guarantees even the stickiest loads will be cleanly dumped.

MODEL	HD10	HD12	HD14
Overall Width	2.40m	2.40m	2.40m
Overall Height	1.95m	2.00m	2.10m
Overall Length	5.20m	5.60m	6.27m
Cubic Capacity	6.4m ³	7.7m ³	10m ³
Wheels	500/45 x 22.5	500/45 x 22.5	500/60 x 22.5
Ram Diameter	107/91/76/61	127/107/91/76/61	127/107/91/76/61
Ram Type	Single 4 Stage Tele	Single 5 Stage Tele	Twin 5 Stage Tele
Axle Type	Tandem	Tandem	Tandem
Axle Size	80mm (8 stud)	90mm (8 stud)	100mm (10 stud)
Tare Weight	4090kg	4350kg	5190kg
Tipping Angle	70°	70°	70°
Tipping Clearance	1.20m	1.20m	1.20m
Brakes	Yes	Yes	Yes
Lights	Yes	Yes	Yes
Sprung Drawbar	Yes	Yes	Yes
Dual Safety Chains	Yes	Yes	Yes