



# TIP TRAILER

## UP TO 10 TONNES

A Giltrap trailer is the first choice for all farmers — the bottom line for quality and dependability.

Giltrap's Tip Trailers will out-perform and outlast any of its competitors with a heritage of good design and proven engineering.

Call 0800 804 458 to find your local dealer.

To view the full list of features and optional extras, visit [www.giltrapag.co.nz](http://www.giltrapag.co.nz).

### KEY FEATURES

- Automatic tailgate release and spreading chains
- Steep 55° tipping angle
- High ground clearance when tipped
- Low deck height
- Rugged front and side boards
- Removable front board
- Sides are hinged and removable
- Built-in tie rails
- Treated 35mm T & G pine deck for excellent durability
- Swivel tow hitch
- Single hydraulic ram to lift efficiently and prevent deck twisting
- Guaranteed to lift evenly distributed stated working load

### OPTIONAL EXTRAS

- Hydraulic tailgate release
- Hydraulic jack
- 5mm steel deck
- 2mm steel overlay floor
- 900mm hay extension
- Brakes
- LED tail lights
- Single axle available on some models, with 400/60 x 15.5 wheels
- Tandem axle with larger wheels available on most models



All Giltrap trailers are designed to tip to at least 55° to fully unload, even with wet or sticky products. A single ram centrally mounted prevents deck twist.



The sides and front board are 3mm steel plate and are very rigid. Sides are hinged so they can be quickly dropped or removed. Giltrap's unique locking system makes this easy.



The oscillating axle design reduces ground compaction and gives a smooth ride across rough ground. The oscillating beam has a strong frame back to the axle centre, to withstand side-turning loads.



The quick-lift telescopic jack can be wound up or down with a full load on the deck.



35mm tongue and groove tanalised pine floor provides a durable, corrosion resistant surface ideal for most applications. 5mm solid steel decks are optional.



The adjustable automatic tailgate release is standard, tripping the tailgate at the desired deck height. It can be upgraded to a hydraulic trip mechanism.

MODEL	T20-05	T23-06	T37-08	T49-10
Deck (L x W)	3.2m x 2.3m	3.65m x 2.3m	3.65m x 2.4m	4.2m x 2.4m
Capacity	2.0m <sup>3</sup>	2.3m <sup>3</sup>	3.3m <sup>3</sup>	4.9m <sup>3</sup>
Rated Lift	5 tonnes	6 tonnes	8 tonnes	10 tonnes
Overall Length	4.3m	4.8m	4.8m	5.75m
Wheels (single)	11.5/80 x 15.3	11.5/80 x 15.3	—	—
Wheels (tandem)	n/a	11.5/80 x 15.3	11.5/80 x 15.3	400/60 x 15.5
Ram Diameter	3.5"	3.5"/2.75"	3.5"/2.75"	107/91/76/61
No. Ram Stages	Single	2 Stage	2 Stage	4 Stage Tele
Side Board Height	300mm	300mm	450mm	500mm
Tare Weight	990kg	1350kg	1630kg	2340kg
Deck Height	900mm	1000mm	1000mm	950mm
Axle Size	60mm (6 stud)	60mm (6 stud)	60mm (6 stud)	70mm (6 stud)
Jack Size	80	80	80	80