



KOHLER[®]
CONFIDANT[™] 19-25 HP

KOHLER[®] Engines

ALL NEW. ALL MUSCLE. READY TO BE UNLEASHED.

Unleash the power of Confidant™ – designed for commercial landscapers and property owners who expect the performance of a professional engine. It's the muscle you can rely on for wide-area walk-behind and stand-on mowers, ZTRs and high-end garden tractors.

PROVEN DURABILITY

- Battle-tested to exceed Kohler commercial duty-cycle demands.
- Dual-seal air filter keeps debris out of the engine.
- Cast iron cylinder bores protect under dirty conditions.
- Pressure lubrication for long engine life.

FAST STARTS & SUPERIOR CUTS

- High-torque inertia drive starter with extra-large output for quick, reliable starting.
- Consistent-Cut™ technology provides more consistent power to your deck, helping you get the perfect cut.

PROFESSIONAL PERFORMANCE

- PRO Performance air, oil, and fuel filters.
- Optional Quad-Clean™ air filtration technology and heavy-duty cyclonic air filter trap fine contaminants for maximum power and engine life.

DESIGNED FOR COMMERCIAL EQUIPMENT REPOWERS

- Available with recoil-start option for wide-area walk-behind mowers.
- High-impact nylon shroud and valve cover protect against bushes and branches damaging internal components.
- Chopper grass screen guard prevents grass and debris packing.

Engine Type	Four-cycle, twin cylinder, overhead valve, air-cooled, gasoline, vertical shaft, aluminum head and crankcase with cast iron cylinder liner.			
Model:	ZT710	ZT720	ZT730	ZT740
Gross Power @ 3600 rpm* Max. hp (kW)	19 (14.2)	21 (15.7)	23 (17.2)	25 (18.6)
Displacement cu in (cc)	44 (725)		46 (747)	
Peak Torque @ rpm ft lb (Nm)	40.0 (54.2) @ 2200 rpm	40.7 (55.2) @ 2200 rpm	40.7 (55.2) @ 2400 rpm	42.4 (57.5) @ 2400 rpm
Oil Capacity U.S. qt (L)	2 (1.9)			
Lubrication	Pressure lubrication with full-flow filter			
Dimensions L x W x H** in (mm)	Standard: 18.8 x 17.5 x 14.9 (478 x 443 x 378) With cyclonic filter: 18.8 x 17.5 x 17.0 (478 x 443 x 431)			
Warranty	2-Year Commercial/3-Year Consumer			

*Horsepower ratings exceed Society of Automotive Engineers Small Engine Test Code J1940. Actual engine horsepower is lower and affected by, but not limited to, accessories (air cleaner, exhaust, charging, cooling, fuel pump, etc.), application, engine speed and ambient operating conditions (temperature, humidity and altitude). For more information, contact Kohler Co. Engine Engineering. Kohler reserves the right to change product specifications, designs and equipment without notice and without incurring obligation.

**Engine measurements based on engine with electric start.

For more information, contact your KOHLER source of supply.
Or call toll-free in the U.S. and Canada 800-544-2444.

Kohler Co., Kohler, Wisconsin 53044 Tel 920-457-4441 Fax 920-459-1570

KohlerEngines.com

© 2013 by Kohler Co. All rights reserved.

Kohler®, Confidant™, Consistent Cut™, and Quad-Clean™ are trademarks of Kohler Co.

KOHLER Engines

Printed in U.S.A. E-2201 10/13