



BERENDS

Grader Blade

"With over 35 years of manufacturing grader blades, this is the strongest mechanical grader blade we have ever produced. You cannot buy better value"

EXTRA HEAVY DUTY RANGE

- Designed to ensure all moving parts are kept tight - vital, as anything loose will eventually wear and break.
- Fitted with high tensile 66mm main pivot. Main and tilt pivots sleeved and greaseable for ease of operation, strength and reduced wear. Sleeved offset pivot points for extra strength. Extensive use of high tensile steels for extra strength in high stress areas.
- Easy to adjust tilt function standard. Tilt below turntable allows tilting angle to remain constant even when fully offset and ensures no decrease in tilting angle if the blade is offset. Replaceable bronze bushes on tilt adjustment.
- Optional hydraulic tilt function makes for even easier operation from the tractor seat.
- 24 angle positions with adjustment from the tractor seat.
- Offsets 4 positions to both right and left allowing blade to work outside the wheel track even at an angle.
- Blade rotates 360 degrees for forwards and backwards operation.
- Curved 10mm mouldboard, reinforced with heavily gusseted corners for strength where it counts and higher clearance. Hardened, reversible cutting edge.
- Almost half a tonne of weight ensures more strength and better penetration of hard surfaces.
- 12 Month Warranty against faulty materials or workmanship.

SPECIFICATIONS E.H.D Grader Blade	7' Model	8' Model
Cutting edge width	7'	8'
Mouldboard Thickness	10mm	10mm
Mouldboard Height	500mm	500mm
Tractor H.P	60-120	60-120
Category - 3 Point Linkage	Cat 2	Cat 2
Nett Weight (kg)	410	425
No. offset positions	8	8
No. angle positions	24	24

Optional extras (at additional cost)

* Wheel kit, 14" holden wheel.

Wheel kit adjustable from the tractor seat and easily removable.

*Hydraulic tilt option - replaces standard ratchet operation.



Manufactured in Australia by

John Berends Implements Pty Ltd

Manufacturers of Agricultural Machinery

130 Frankston-Dandenong Rd, Dandenong South 3175 Victoria Australia

Phone: 03 9791 2494

Fax: 03 9794 5568

ABN 79007035369

* Due to our policy of continuous improvement, machines may differ from those illustrated. We reserve the right to change design and/or specifications without prior notice or obligation.