



BERENDS

Slashers

" A rugged, extra tough slasher built to take real punishment from continuous work - ideal for contractors. "

THE E.H.D. RANGE

- Extra strong build with exceptionally strong perimeter and centre crossmembers - where it counts!
- Headstock made from heavy angle and RHS and fitted with floating (toggle) top link as standard.
- The rotor beam is manufactured from hardened and tempered 100mm x 12m spring steel.
- Comes standard with an extra heavy duty 110 H.P European precision gearbox, and heavy duty A8 PTO shaft with 4 plate adjustable clutch.
- Available in two models the EHD180 and EHD210.
- Full 12 Month Warranty.

SPECIFICATIONS E.H.D Slasher	Model	
	EHD180	EHD210
Cutting width	1.75m	2.05m
Cutting height (with adj skids)	25-100mm	25-100mm
Weight	600kg	635kg
Length (Overall)	1.95m	2.20m
Width (Overall)	1.96m	2.20m
Height (to top of g/box guard)	670mm	670mm
Headstock	Rigid - floating top linkq	Rigid - floating top link
Body Construction	5mm Top Plate	5mm Top Plate
	6mm skirt	6mm skirt
Tractor H.P range	60-120	75-130
PTO/Adj. slip clutches	A8	A8
Gearbox/PTO speed	110 H.P. (540rpm)	110 H.P. (540 rpm)
Category - 3 Point Linkage	Cat 2	Cat 2
Alignment (Offset is 9" to RHS)	o/set or c/l	o/set or c/l
Skids	Adjustable	Adjustable
Blades	straight (reversible) or stepped	

Optional extras (at additional cost)

- * Wheel Kit - Solid rubber, castors 360 degrees.
- * Front and rear safety chains or flaps



Manufactured in Australia by

John Berends Implements Pty Ltd

Manufacturers of Agricultural Machinery

130 Frankston-Dandenong Rd, Dandenong South 3175 Victoria Australia

Phone: 03 9791 2494 Fax: 03 9794 5568

ABN 79007035369

* Due to our policy of continuous improvement, machines may differ from those illustrated. We reserve the right to change design and/or specifications without prior notice or obligation.