

BERENDS

Grader Blade



"When extra strength is needed"

HEAVY DUTY RANGE

- Fitted with high tensile 50mm main pivot (adjustable for wear), high tensile turntable, and pivot pins 40-50mm wide to minimise wear and avoid breakage.
- 24 angle positions with adjustment from the tractor seat.
- Offsets 4 positions to both right and left allowing blade to work outside the wheel even at an angle.
- Blade rotates 360 degrees for forwards and backwards operation.
- Curved 10mm thick mouldboard for strong cuts at the correct angle, and high clearance for greater capacity. Hardened, reversible cutting edges (as used on road graders).
- 12 Month Warranty against faulty materials or workmanship.

SPECIFICATIONS Heavy Duty Grader Blades	6' Model	7' Model	8' Model
Cutting edge width	6'	7'	8'
Mouldboard Thickness	10mm	10mm	10mm
Mouldboard Height	500mm	500mm	500mm
Tractor H.P	40-100	40-100	40-100
Category - 3 Point Linkage	Cat 1/2	Cat 1/2	Cat 1/2
Nett Weight (kg)	305	350	370
No. offset positions	8	8	8
No. angle positions	24	24	24

Optional extras (at additional cost)

* Wheel kit, 14" holden wheel.

Wheel kit adjustable from the tractor seat and easily removable.



Manufactured in Australia by

John Berends Implements Pty Ltd

Manufacturers of Agricultural Machinery

130 Frankston-Dandenong Rd, Dandenong South 3175 Victoria Australia

Phone: 03 9791 2494 Fax: 03 9794 5568

ABN 79007035369

* Due to our policy of continuous improvement, machines may differ from those illustrated. We reserve the right to change design and/or specifications without prior notice or obligation.