

**5 YEAR
WARRANTY
ON ITALIAN
GEARBOXES**

Hydraulic Post hole diggers

Model	Hydraulic Model
PTO shaft	Series 3/L3 torque limiting clutch
Gearbox	85 HP
Main frame	100 x 100 x 6mm
Tractor HP required	30-100 HP
Nett weight less auger	150kg



Hydraulic Model with 12" Auger
(NB- Not fitted with control lever as shown)

- Fitted with heavy duty European gearbox and torque limiting PTO shaft.
- 2 1/2" x 8" hydraulic ram transfers approximately 1000kg of weight from the tractor onto the auger. Ideal for penetrating hard ground.
- Main boom and 'A' frame are heavier to accommodate the hydraulic ram and hoses.
- Digs to a maximum 4' (1200mm) depth if ground conditions permit.
- Auger sizes - 6", 8", 10", 12", 15", 18", and 24".
- All models are fitted with jib hook and transport chain as standard.
- 12 month warranty against faulty materials or workmanship.

Augers



All Augers are fitted with the Pengo Boring Head with replaceable earth teeth and pilots. The 6" and 8" augers are a single cutting head and the 10", 12", 15" 18" and 24" are a double cutting head. Optional teeth and pilots are available to suit various ground conditions.



Earth teeth (1781) fitted as standard on auger



Bolt-on earth pilot (1785) fitted as standard on auger. Also available in tungsten tipped (1786)



Tungsten tipped (1782) or tungsten hard faced (1692) teeth for high wearing abrasive conditions.



Carbide insert teeth (1796) for extremely abrasive soils. Best used in inside pockets only.



Serrated tungsten tipped (1783) teeth suitable for areas where high penetration



Chisel teeth (1780) for high penetration in loose rock or compact soil. Also available with tungsten tip (1789) for abrasive soils.



JOHN BERENDS IMPLEMENTS Pty Ltd

130 Frankston-Dandenong Rd, Dandenong

Tel: (03) 9791 2494 Fax: (03) 9794 5568

Email: berends@johnberendsimplements.com.au