

SLR FEEDER

The Giltrap SLR Feeder can effectively and efficiently feed out different variations of round and square bales.



KEY FEATURES

- A unique 2 stage sequence-controlled bale loading system that lifts the bale, holds it in position to assist with string/ wrap removal, and then places the bale in the correct position on the tilting tray
- Built to Giltrap's high standard for reliability and long-life performance
- Unique feed elevator with anti-wrap guard
- A position indicator linked to the loading mechanism to assist the operator with lifting the second bale

- String loop to assist removal of bale string
- Heavy duty powder coated full sheet metal floor
- High tensile bale forks for ease of loading
- Wide rear axle width (2.2 metres) for stability
- Minimal moving parts with all pivot points bushed and greased
- Safety chains

Call 0800 804 458 to find your local dealer.
To view the full list of features and optional extras, visit www.giltrapag.co.nz





Length (mm)	5475
Width (mm)	2910
Height (mm)	2250
Weight (unladen) (kg)	1275
Max./ bale size (round)	6ft diameter
Max. bale size (square)	4.6ft x 6ft (x 8ft long)

FEATURES



Feeds round or square bales equally well.



The loading system suspends the bale above the feeding deck to simplify the removal of net and plastic and wrap.



The feed platform is raised and lowered by the operator to control the feed rate.