

BERENDS



THE WARRIOR SLASHER

"The strongest slasher in the range – ideal for contractors"

- Extra strong build with exceptionally strong perimeter and centre cross-members – where it counts!
- Headstock made from heavy angle and RHS and fitted with floating (toggle) top link as standard.
- Unlimited horse-power gearbox with unbreakable 90mm output shaft, and heavy duty Series 8 PTO shaft with 4 plate adjustable slip clutch.
- Rotor beam is manufactured from hardened and tempered 100mm x 12mm spring steel. Twisted and stepped blades create an updraft effect which lifts grass flattened by tractor wheels.
- Optional solid rubber wheel-kits, front and rear safety chains or flaps are also available. Full 12 month warranty against faulty materials or workmanship.

SPECIFICATIONS	Warrior 180	Warrior 210
Cutting width	1.75m	2.05m
Cutting height (with adj skids)	25-100mm	25-100mm
Weight	700kg	805kg
Length (Overall)	1.95m	2.20m
Width (Overall)	1.95m	2.20m
Headstock	Rigid - floating top link	Rigid - floating top link
Body construction	5mm body, 6mm sides	5mm body, 6mm sides
Tractor HP range	100 HP+	100 HP+
PTO	Series 8 shaft with 4 plate slip clutch	
Gearbox/PTO speed	No maximum rating. Unlimited Horse power	
Alignment	Centre-line/Offset	Centre-line/Offset
Skids	Adjustable	Adjustable
Blades	75mm x 16mm stepped and twisted	
Tractor Cat connection	Cat 2	Cat 2



Manufactured in Australia by

John Berends Implements Pty Ltd

Manufacturers of Agricultural Machinery

130 Frankston-Dandenong Rd, Dandenong South 3175 Victoria Australia

Phone: 03 9791 2494 Fax: 03 9794 5568

Email: berends@johnberendsimplements.com.au Website: www.johnberendsimplements.com.au

ABN 79007035369

* Due to our policy of continual improvement, machines may differ from those illustrated. We reserve the right to change design and/or specifications without prior notice or obligation.