

WestAir

AIR COMPRESSORS

ELECTRIC AIR COMPRESSORS

12 & 24 VOLT

Compact, heavy duty oil lubricated air compressors with aluminium piston for 4WD or truck and industrial applications.



MODEL	DISP CFM	DISP L/M	FAD CFM	FAD L/M	HP	CYL	Tank (Ltr)	Weight (Kg)	Dimensions (LxWxH cm)
DC12	4	113	1.3	37	0.5	1	n/a	7.5	33 x 12 x 21
DC1208-01	4	113	1.3	37	0.5	1	8	16	42 x 38 x 33
DC24	5.5	142	2.6	74	0.5	1	n/a	7.5	33 x 12 x 21
DC2408-01	5.5	142	2.6	74	0.5	1	8	16	42 x 38 x 33

DIRECT DRIVE

Reliable & lightweight home handyman air compressors for domestic use. Has an alloy pump with cast iron cylinder and inbuilt regulator.



MODEL	DISP CFM	DISP L/M	FAD CFM	FAD L/M	HP	CYL	Tank (Ltr)	Weight (Kg)	Dimensions (LxWxH cm)
WED10/24	6.8	192	3.7	105	2	1	25	25	59 x 30 x 59
WED12/35	7.7	218	4.3	122	2.5	1	35	27	62 x 32 x 66

SINGLE PHASE

Heavy duty air compressors suitable for home and industrial applications. Slow revving cast iron pump and fully adjustable German Condor pressure switch.



MODEL	DISP CFM	DISP L/M	FAD CFM	FAD L/M	HP	CYL	Tank (Ltr)	Weight (Kg)	Dimensions (LxWxH cm)
WE12	12	340	9	255	2.2	2	70	69	94 x 32 x 73
WE18	16	453	11.3	320	3	3	70	82	94 x 32 x 76
WE18/120*	16	453	11.3	320	3	3	116	127	128 x 46 x 84

* All 116Ltr tanks and larger are skid mounted stationary units

THREE PHASE

Heavy duty, high output air compressors engineered to handle the most demanding industrial applications. Large slow revving cast iron twin & 3 cylinder pumps with fully adjustable German Condor pressure switches.



MODEL	DISP CFM	DISP L/M	FAD CFM	FAD L/M	HP	CYL	Tank (Ltr)	Weight (Kg)	Dimensions (LxWxH cm)
WA20/120	18.6	526	13.4	379	4	3	116	146	128 x 46 x 84
WA27/120	26.1	739	18.6	526	5.5	2	116	199	128 x 46 x 94
WA35/120	35.4	1002	28	792	7.5	3	116	222	128 x 46 x 94
WA27/200	26.1	739	18.6	526	5.5	2	200	245	147 x 53 x 103
WA35/200	35.4	1002	28	792	7.5	3	200	268	147 x 53 x 103
WA45/300	46.5	1316	37.8	1070	10	3	300	290	180 x 54 x 109
WA65/300*	64.1	1814	54	1528	12	3	300	370	180 x 60 x 125

* WA65/300 comes standard with Star Delta Starter & solenoid valve

WARRANTY

12 Months on 12/24 Volt & Direct Drive Units | 12 Months on Motors | 3 Years on Belt Drive Pumps | 5 Years on Tanks

Toll Free Call: 1800 559 501 www.westaircompressors.com.au

WestAir

AIR COMPRESSORS

PETROL & DIESEL AIR COMPRESSORS

HONDA DIRECT DRIVE PETROL

POWERED by
HONDA



WP14DD

MODEL	DISP CFM	DISP L/M	FAD CFM	FAD L/M	ENGINE	CYL	Tank (Ltr)	Weight (Kg)	Dimensions (LxWxH cm)
WP14DD	13.5	382	4.2	119	GX160	1	16*	35	56 x 48 x 47

* Twin tanks - 2 x 8Ltr tanks (as pictured)

HONDA PETROL

- Slow revving cast iron pump - high volume; fast recovery
- US Conrader auto idle; 135PSI cut out

POWERED by
HONDA



WP20/70



MODEL	DISP CFM	DISP L/M	FAD CFM	FAD L/M	ENGINE	CYL	Tank (Ltr)	Weight (Kg)	Dimensions (LxWxH cm)
WP16/70	13.7	388	9.9	280	GX160	2	70	76	94 X 32 X 73
WP20/70	20.2	571	14.7	416	GX160	3	70	83	94 X 32 X 76
WP20/120	20.2	571	14.7	416	GX160	3	116	128	128 X 46 X 84
WP27/120	26.1	739	18.6	526	GX270	2	116	171	128 X 46 X 94
WP38/120	37.6	1064	29	821	GX390	3	116	191	128 X 46 X 94
WP48/120	48.1	1361	40.2	1138	GX390	3	116	193	128 X 46 X 98

KOHLER PETROL

- Slow revving cast iron pump - high volume; fast recovery
- US Conrader auto idle; 135PSI cut out
- Full 3 year warranty on all Kohler engines

KOHLER.ENGINES



WP30/130K

MODEL	DISP CFM	DISP L/M	FAD CFM	FAD L/M	ENGINE	CYL	Tank (Ltr)	Weight (Kg)	Dimensions (LxWxH cm)
WP20/70K	20.2	571	14.7	416	CH270	3	70	83	94 x 32 x 76
WP30/120K	32.4	917	23.6	668	CH395	3	116	191	128 x 46 x 94
WP50/120K	52.6	1489	41.4	1172	CH440	3	116	193	128 x 46 x 98

Please Note: All Kohler Petrols come with electric start engines, complete with battery & leads as standard

KOHLER DIESEL

- Slow revving cast iron pump - high volume; fast recovery
- US Conrader auto idle; 135PSI cut out
- Italian manufactured Kohler diesel engines with full 3 year warranty

KOHLER.ENGINES



WD20/70

Standard electric start on all Kohler engines

MODEL	DISP CFM	DISP L/M	FAD CFM	FAD L/M	ENGINE	CYL	Tank (Ltr)	Weight (Kg)	Dimensions (LxWxH cm)
WD16/70	13.7	388	9.9	280	15KD225	2	70	80	100 x 48 x 75
WD20/70	20.2	571	14.7	416	15KD225	3	70	90	100 x 48 x 75
WD20/120	20.2	571	14.7	416	15KD225	3	116	130	128 x 46 x 88
WD27/120	26.1	739	18.6	526	15KD350	2	116	179	128 x 46 x 95
WD38/120	37.6	1064	29	821	15KD440	3	116	205	147 x 53 x 103
WD48/120	48.1	1361	40.2	1137	15KD500	3	116	207	147 x 53 x 103

Please Note: All Kohler Diesels come with electric start engines, however NO battery or leads are supplied

DISP CFM: Displacement Cubic Feet per Minute (CFM) is the theoretical maximum volume of air which can be delivered by the air compressor pump.
FAD CFM: Free Air Delivery Cubic Feet per Minute (CFM) describes the actual volume of air which is available for use at the exit port of the air compressor tank; (L/M = Litres per Minute)

WARRANTY: 12 Months on Direct Drive Units | 3 Years on Belt Drive Pumps | 5 Years on Tanks | Manufacturers on Engines