









PROUDLY AUSTRALIAN MADE



SPECIFICATIONS

5000 P.S.I. (350 Bar) Pump Pressure 6000 P.S.I. Turbo Pressure (Optional) 23 Litres per minute Pump Volume GX660 25 H.P Engine Class Honda Petrol Motor 1450 RPM Industrial Machine Electric Start, Hour Meter

STANDARD EQUIPMENT

10 Metres High Pressure Hose Insulated On/Off Pistol Assembly Single Lance Assembly W/- Fixed Fan Jet Operators and Parts Manuals

FEATURES		BENEFITS
Interpump with Ceramic Pistons and Brass Head, 1450RPM Low Speed	→ →	Longer pump life, non corrosive pump head Reduced maintenance costs
Oz-tuff Belt Drive	\rightarrow	15% more power available than a gearbox No more Gearbox Oil Leaks (maintenance free)
Water By-Pass Cooling Tank	→	Reduces potential damage to the pump in bypass
Inlet Water Filter	→	Stops debris from scoring pistons and seals
Pressure Gauge	→	Easily monitor pump performance
Powder Coated Zinc Annealed	→	Resistant to corrosion
Chassis	→	Greater manoeuvrability over tough terrain
Roll Frame with Lifting Hook		
4 Pneumatic Wheels		