

GENERATING SET GE 4000 LDS/GS



- Lombardini, diesel engine
- Manual recoil with automatic decompression
- Synchronous alternator
- Overload protection and Ground Fault Interrupter
- Battery charger 12V - 10A with thermal protection
- Two socket 230V single-phase
- Portable
- Trolley (option)
- Meets EEC directives

Standard equipment



Diesel engine



Air cooling



Manual recoil



Synchronous alternator



Socket 230V Schuko



Ground fault interrupter



Thermal shut off



Battery charger

Options on request



● Plug 230V 16A 2PT (Schuko)

● Earthing kit MT10

● Trolley CTM6000

Technical Data

GE 4000 LDS/GS

A.C. GENERATION	50 Hz, synchronous, single-phase, self-excited, self-regulated, brushless
Single-phase generation	3.6 kW / 230 V / 15.7 A
Battery charger d.c.	12V - 10A
Duty cycle	100%
Power factor (Cos φ)	1
Insulation class	H
ENGINE	Gasoline, 4-stroke, air cooled
Type	Lombardini 15LD350
Output*	4.6 kW (6.3 HP)
Speed	3000 rpm
Displacement	349 cm ³
Cylinders	1
Fuel consumption	260 g/kWh
* Maximum output according to ISO 3046/1	
GENERAL SPECIFICATIONS	
Tank capacity	4.3 l
Runnig time (Load 75%)	4.2 h
Protection	IP 23
Dimensions Lxwxh (mm)	785x410x515
Weight	64 kg
Noise level **	100 LWA (75 dB(A) - 7 m)
** LWA conforms to EEC Directive 536	

Values shown are nominal values. For further information please contact the sales department.