

## GENERATING SETS GE 7500 HSX (EAS)

- Honda OHV gasoline engine
- Engine protection (oil)
- Three-phase synchronous alternator
- Circuit breaker / GFI - ELCB
- Sockets EEC: 1x400V/16A 3P+N+T - 1x230V/16A 2P+T
- Prepared for connection to Automatic transfer unit
- Meets EEC directives



Standard equipment										
	Gasoline engine	Air cooling	Electric starter	Battery 12V	Engine shut down (oil)	Hour counter	Low fuel indicator	Bat.-charge thermal	Ready for EAS/TCM	Start local / Remote selector
Options on request										
	Synchronous alternator	Compound	Voltmeter	EEC sockets	Circuit breaker	Ground fault interrupter				
	● Plugs 400/230V		● Automatic transfer unit EAS15B-806				● CTM7 (4 wheels)			
			● Earthing Kit MT10				● Kit exhaust extension			

### Technical Data

### GE 7500 HSX (EAS)

**A.C. GENERATION** 50 Hz, synchronous, three-phase, self-excited, self-regulated, brushless

<b>Three-phase power (max)</b>	7.5 kVA (6 kW) / 400 V / 10.8A
<b>Three-phase power (continuous)</b>	6.5 kVA (5.2 kW) / 400 V / 9.4A
<b>Single-phase power</b>	4 kVA (4 kW) / 230 V / 17.4A
<b>Duty cycle</b>	100%
<b>Cos φ</b>	0.8
<b>Insulation class</b>	H

On request other voltages and frequencies (60 Hz)

**ENGINE** Gasoline, 4-stroke, air cooled

<b>Type</b>	HONDA GX 390
<b>Net power</b>	7.7 kW (10.3 HP)
<b>Speed</b>	3000 rpm
<b>Displacement</b>	389 cm <sup>3</sup>
<b>Cylinders</b>	1
<b>Fuel consumption (Load 75%)</b>	2.15 l/h - 313 g/kWh

**GENERAL SPECIFICATIONS**

<b>Tank capacity</b>	20 l
<b>Running time (Load 75%)</b>	9.5 h
<b>Protection</b>	IP 23
<b>Dimensions Lxwxh (mm) *</b>	1060x570x665
<b>Weight *</b>	165 kg
<b>Measured acoustic power **</b>	88 LWA (63 dB(A) - 7 m)
<b>Guaranteed acoustic power **</b>	89 LWA (64 dB(A) - 7 m)

\* Dimensions and weight are inclusive of all parts without optional CTM \*\* Acoustic power according to 2000/14/CE

**Values shown are nominal values. For further information please contact the sales department.**