

The COSMO Bully M120 Champion Series Power Harrows have been designed and engineered in Europe and are a serious machine for professional operators.

They are robust, with a two piece rigid frame, available in 2.5m and 3.0m widths.

The blade design and action results in soil being finely worked to the maximum depth (280mm) in fewer passes, minimising ground compaction, reducing fuel consumption and placing less load and demands on the tractor.





Options include rear cage or packer rollers (packer rollers shown in photo above) and a quick fit blade system.



Code	TM120/160-250	TM120/160-300
Description	Bully M120-250 Champion Series Power Harrow	Bully M120-300 Champion Series Power Harrow
Gearbox	160hp, 540/1000rpm, multi speed	
PTO shaft/clutch	Series W2600 with 200mm (8") friction (slip) clutch	
Rear levelling bar	Manual, mechanical, adjustment	
Side plates	8mm, floating and/or height adjustable	
Finish	Powder coated	
Total no. of blades	20	24
No. of rotors	10	12
Rotor speeds	343 - 376 at 540rpm   334 - 369 at 1000rpm	
Blades	285x12mm	
Linkage	Category 2 and 3	
Guarding	Standard with CE guards	
Overall width (mm)	2600	3100
Working width (mm)	2500	3000
Working depth (mm)	280	
Tractor range (hp)	100 - 140	120 - 140
Weight (kg)	850	950

Options		
Code	TM120/160-250CR	TM120/160-300CR
Description	Bully M120-250 Cage Roller	Bully M120-300 Cage Roller
Design	Ø450mm, eight (8) bar, mechanical adjustment	
Weight (kg)	145	166
Code	TM120/160-250PR	TM120/160-300PR
Description	Bully M120-250 Packer Roller	Bully M120-300 Packer Roller
Design	Ø500mm with teeth (80mm), scrapers, mechanical adjustment	
Weight (kg)	305	360

M120 Power Harrow blade (right) M120 Power Harrow blade (left) 6533 6532

M120 Power Harrow quick fit blade (right) M120 Power Harrow quick fit blade (left) 6659 6658