

Hydraulic Post Hole Digger

The KANGA XH Range Post Hole Diggers are a hydraulic assist, down pressure digger engineered for category 2, 3-point linkage tractors that are rated 40 to 100hp.

This post hole digger has been designed that, when the frame is in the correct position, the lower linkage arms of the tractor 'lock' the frame in place and digging (raising and lowering the auger) is done using the 3" hydraulic ram ONLY.

In the event the operator forgets to use the ram and uses the tractor linkage instead, shear bolts have been incorporated into the design as a safeguard against damage.

Available with either a 50hp or 75hp gearbox, the KANGA XH Range Post Hole Digger is a fully welded, reinforced and gusseted, 6mm square tube, dual rail frame.

Australian made and sold separately, the double cut augers are 1.2m in length and, ground conditions permitting, result in hole depths of up to 1.1m.

Refer to page 77 for details of augers.



Code	KPHD50-XH	KPHD75-XH
Description	50hp XH Range Post hole Digger	75hp XH Range Post hole Digger
Construction	Heavy duty, dual rail frame, steel sq. tube, fully welded and gusseted	
Linkage/Mounting	Category 2, height adjustable bolt-on pins	
Gearbox	50hp, 540rpm, 3.18:1 reduction ratio	75hp, 540rpm, 4.1:1 reduction ratio
PTO shaft/clutch	Series 4 with 150mm (6") 40hp friction (slip) clutch	Series 4 with heavy duty 150mm (6") 80hp friction (slip) clutch
Finish	Powder coated	
Tractor range (hp)	40 - 70	50 - 100
Weight (kg)	200	210