



Cosmo Bully

UH Series Rotary Hoe

The European designed COSMO Bully UH Series Rotary Hoes are single speed, gear driven implements specifically for tractors 50 to 75hp.

Engineered to include many features and accessories traditionally found in much larger rotary hoes, the COSMO Bully UH Series is suitable for a range of horticultural and gardening applications including nurseries, vineyards and orchards.

The rotor, with a diameter of 480mm blade to blade, features six (6) C shaped, heat treated blades (per flange) in a speed configuration.

This design, where the blades are slightly staggered from flange to flange, reduces the tractor horsepower required to till a high volume of soil in a wide range of soil types and conditions.



Code	TBUH60	TBUH72	TBUH84
Description	Bully UH60 Rotary Hoe	Bully UH72 Rotary Hoe	Bully UH84 Rotary Hoe
Side transmission	Gear drive		
Gearbox	75hp, 540rpm, single speed		
PTO shaft/clutch	Series 6 with 200mm (8") friction (slip) clutch		
Skids	Height adjustable		
Finish	Powder coated		
Rotor diameter (mm)	480		
Rotor speed (rpm)	241		
No. of rotor flanges	7	8	9
No. of blades p/flange	6	6	6
Total no. of blades	42	48	54
Blades	Curved/speed		
Linkage	Category 1 and 2		
Guarding	Standard with CE guards		
Overall width (mm)	1834	2063	2292
Working width (mm)	1680	1910	2140
Working depth (mm)	190		
Tractor range (hp)	50 - 75	55 - 75	60 - 75
Weight (kg)	390	420	450

Parts

- 3127 UH curved/speed blade (right)
- 3126 UH curved/speed blade (left)
- 1372 UH square/L shaped blade (right)
- 1373 UH square/L shaped blade (left)