



# Cosmo Bully

## UL Series Rotary Hoe

The European designed, COSMO Bully UL Series Rotary Hoes are gear driven implements for compact and sub-compact tractors up to 40hp (max.).

Engineered to till soil in nurseries, vineyards, orchards and hobby farms, they are ideal for owner operators.

The rotor features six (6) C shaped, heat treated blades (per flange) in a speed configuration.

The speed configuration, a design where the blades are slightly staggered from flange to flange, reduces the horsepower required to produce a fine finish in a variety of soil conditions.



Code	TBUL36	TBUL48	TBUL60
Description	Bully UL36 Rotary Hoe	Bully UL48 Rotary Hoe	Bully UL60 Rotary Hoe
Side transmission	Gear drive		
Gearbox	40hp, 540rpm, single speed		
PTO shaft/clutch	Series 4 with 150mm (6") friction (slip) clutch		
Skids	Height adjustable		
Finish	Powder coated		
Rotor diameter (mm)	375		
Rotor speed (rpm)	245		
No. of rotor flanges	4	6	7
No. of blades p/flange	6	6	6
Total no. of blades	24	36	42
Blades	Curved/speed		
Linkage	Category 1 (quick hitch compatible)		
Guarding	Standard with CE guards		
Overall width (mm)	1035	1340	1645
Working width (mm)	915	1220	1525
Working depth (mm)	165		
Tractor range (hp)	15 - 28	20 - 35	30 - 40
Weight (kg)	153	180	200

### Parts

- 14040 UL curved/speed blade (right)
- 14141 UL curved/speed blade (left)
- 14124 UL square/L shaped blade (right)
- 14125 UL square/L shaped blade (left)